

HALDRUP C-90

Plot combine

The Haldrup C-90 plot combine has a high harvesting capacity and is able to work properly even under severe conditions, through its ruggedness.



TECHNICAL DETAILS

Cabin	For 2 persons with air condition	Lower sieve	Louwer sieve 15 mm – (adjustable louver sieve distance) 1140 mm x 850 mm
Engine	Deutz Diesel, water cooled, 80 kW, 108 HP	Total sieves area	1.92 m ²
Fuel tank	200 l	Bottom blower speed	300 - 1100 U/min; adjustable with variator
Drive	Hydrostatic transmission 0 - 20 km/h	Cutting table	Width: 1250 - 1510 - 1740 - 2045 - 2350 - 3010 mm cutting table with hydraulic drive - 5 reel bars
Steering	Hydraulic; steering wheel adjustable in height and inclination	Maize header Geringhoff	2 rows
Tyres (rear)	23 x 8.50 - 12 8PR or 11.0/65 - 12 8PR or 10.0/75 - 15.3	Tine cloth pick-up device	1510 - 1740 - 2045 - 2350 - 3010 mm
Tyres (front)	335/80 R18 or 405/70 R20 or 440/65R24	Options	HarvestManager, HarvestMaster, NIRS, volume box, moisture measurement, camera surveillance, sunflower harvester, corn harvester, GPS
Threshing drum	Speed: 450 - 1800 U/min Inlet width: 450 mm number of rasp bars: 6	Dimensions length - width - height	From 7600 mm - 2360 mm 3100 mm
Concave	Wire distance: 7 mm - 11 mm - 26 mm	Weight	From 5500 kg
Straw walkers	3 or 4 straw walkers		
Upper sieve	Louwer sieve 22 mm – (adjustable louver sieve distance) 1140 mm x 850 mm		

GERMANY | HALDRUP GmbH

Justus-von-Liebig-Straße 3 | 74532 Ilshofen
Tel.: +49 (0) 7904 943998 0 | Fax: +49 (0) 7904 943998 660
Mail: info@haldrup.net | www.haldrup.net

FRANCE | HALDRUP SARL

14 rue des peupliers | 72190 Sargé-lès-le-Mans
Tel.: +33 (0) 243 8944 95 | Fax: +33 (0) 234 0871 50
Mail: info@haldrup.net | fr.haldrup.net

DENMARK | HALDRUP GmbH

Havnevej 90 | 9670 Løgstør
Tel.: +45 (0) 98 671 033
Mail: info@haldrup.net | www.haldrup.net

USA | HALDRUP USA Corp.

1725 Hillcrest Drive | Ossian, IN 46777
Tel.: +1 844 694 6205 | Fax: +1 866 750 7590
Mail: info.usa@haldrup.net | usa.haldrup.net