

## HALDRUP C-90

Plot combine

The Haldrup C-90 plot combine has a high harvesting capacity and is able to work properly even under severe conditions, through its ruggedness.



### TECHNICAL DETAILS

Cabin	for 2 persons with air-condition	Lower sieve	Louver sieve 15 mm – (adjustable louver sieve distance) 1140 x 850 mm
Engine	Deutz Diesel, water cooled, 80 kW, 108 HP	Total sieves area	1,92 m <sup>2</sup>
Fuel tank	200 l	Bottom blower speed	300 - 1100 U/min; adjustable with variator
Drive	hydrostatic transmission 0-20 km/h	Cutting table	Width: 1250 - 1510 - 1740 - 2045 - 2350 - 3010 mm cutting table with hydraulic drive - 5 reel bars
Steering	hydraulic; steering wheel adjustable in height and inclination	Maize header Geringhoff	2 rows
Tyres (rear)	23x8.50-12 8PR or 11.0/65-12 8PR or 10.0/75-15.3	Tine cloth pick-up device	1250 - 1510 - 1740 - 2045 - 2350 - 3010 mm
Tyres (front)	335/80 R18 or 405/70 R20 or 440/65R24	Options	HarvestManager, HarvestMaster, NIRS, volume box, moisture measurement, camera surveillance, sunflower harvester, corn harvester, GPS
Track width	1415 mm	Dimensions: Length - width - height	from 7600 mm - 2360 mm - 3100 mm
Threshing drum	speed: 450 - 1800 U/min inlet width: 450 mm number of rasp bars: 6	Weight	from 5.500 kg
Concave	wire distance: 7 mm - 11 mm - 26 mm		
Straw walkers	3 or 4 straw walkers		
Upper sieve	Louver sieve 22 mm – (adjustable louver sieve distance) 1140 x 850 mm		